



Leading Features

- ▶ Three phase output
- ▶ Over 97.5% Max. efficiency
- ▶ 200V – 800V input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 year standard, 8 year premium warranty, or extended options



Ginlong Technologies Co.,Ltd

Address: No. 57 Jintong Road, Binhai Industrial Park, Xiangshan,
Ningbo, Zhejiang, 315712, China

Tel: +44 (0)113 328 0870 +86 (0)574 6578 1806 Fax: +86 (0)574 6578 1606

Email: info@ginlong.com Web: www.ginlong.com



solis australasia pty ltd

Address: 5/ 109 Tulip Street Cheltenham,
Victoria, 3192 Australia

Tel: +61 (0)3 8555 9516
Email: service@ginlongaust.com.au

Web: www.solisinverters.com.au

Data Sheet



Model	Solis-6K	Solis-10K	Solis-15K
Energy source	PV		
Input Side			
Max. DC input voltage (V)	1000		
Start-up DC input voltage(V)	330		
MPPT operating range(V)	200-800	300-800	
Rated DC voltage(V)	400		600
Max. DC input current(A)	15+15	18+18	
Number of MPP/Max strings per MPPT	2/2		
Output Side			
Rated output power(kW)	6	10	15
Max. transient power(kW)	6.6	11	15
Rated AC grid voltage(V)	380/400/480		
AC grid voltage range(V)	313-470(adjustable)		
Operating phase	three		
Rated AC grid output current(A)	9.1/8.7/7.2	15.2/14.5/12.0	22.8/21.7/18.0
Max. AC output current(A)	10.5/10.0/7.9	16.7/16.0/13.2	25.1/23.1/19.8
Output power factor	>0.99		
Grid current THD	Total THD<4%		
DC injection current(mA)	<20		<50
Rated grid frequency(Hz)	50/60		
Efficiency			
Max. efficiency	>97.5%		
Euro efficiency	>96.5%		
MPPT efficiency	>99.9%		
Protection			
Temperature protection	Yes		
DC reverse-polarity protection	Yes		
AC short circuit protection	Yes		
AC output overcurrent protection	Yes		
Output overvoltage protection-Varistor	Yes		
Ground fault monitoring	Yes		
Grid monitoring	Yes		
Islanding protection	Yes		
Integrated DC switch	Optional		
General data			
Size(mm)	430W*600H*220D		
Weight(kG)	27.0	30.0	
Topology	Transformerless		
Internal consumption	<1W (Night)		
Running temperature	-25°C~60°C		
Ingress protection	IP65		
Operating range utility frequency (Hz)	47-52 or 57-62(adjustable)		
Noise emission(typical)	<30 dBA		
Cooling concept	Natural convection	Forced air cooling	
Max.operating altitude without derating	2000m		
Designed lifetime	>20 years		
Utility monitoring	Islanding protection V_{AC} , F_{AC} in accordance with UL 1741, G59/2, AS4777, VDE 0126-1-1		
Operating surroundings humidity	0~95%		
EMC	EN61000-6-1:2007	EN61000-6-3:2007	
Features			
DC Connection	MC-4 mateable		
AC Connection	IP67 rated plug		
Display	LCD, 2 x 20 Z.		
Interface	RS 485, WiFi/GPRS (optional)		
Warranty	5~10 Years		